

2M805 Micro-Miniature High Speed Double Flange Standoff

FEATURES

- + PC Tail Contact Termination
- + Tri-Start Threads
- + Threaded Mounting Holes
- + PFA Teflon Inserts
- + Optimized Contacts For High Speed Applications

OVERVIEW

Amphenol offers customized 2M receptacles with double flange standoffs. This enhanced design allows the user to mount to PC board applications. This series of connectors is ideal for high speed data bus applications utilizing PFA (Teflon) inserts and optimized contacts for high speed capability.



Part Number Guide

1. Finish	2. Shell Styles/Size	3. Shell Size – Insert arrangement	4. Contact Type
F9-	72334F-	19	A

Step 1. Select a Finish

	Designates
F9-	Thick OD Cadmium Nickel Base
F2-	Black Zinc Nickel
FH-	Thick Electroless Nickel
MT-	Durmalon

Step 2. Select a Shell Style

	Designates
72334F-	Jam Nut Rear Panel Mount Size 11

Step 3. Insert Arrangement

	Designates
19	11-19 Insert Arrangement

Step 5. Select a Contact Type

Contact Type/Key Way Position		
Shell Key Way	Pin PC Tail	Socket PC Tail
A	P	S
B	G	H
C	I	J
D	K	L

CONTACT US:

Anthony Annunziata
E-mail: aannunziata@amphenol-aa.com
Phone: 607-563-5532

Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors.

AMPHENOL is a registered trademark of Amphenol Corporation. ©2014 Amphenol Corporation REV:12/19/2014