	4	3	
21-033430-021 SHEET 1 OF 1 A			
	Ø.182 MAX → ►		
С			
	.060 OUTER TAIL		
В	✓ . 151 MAX — ►	INNER TAIL	(1) 2 0±.0 0
			5
	4. INDICATED DIMENSION TO BE FROM REAR SHOULDER TO POINT OF ENGAGEMENT OF A .0940 \pm .0002 DIA SQUARE ENDED PIN.	CONTACT AND	
	3. PACKAGE PER PRODUCTION SHEET. HANDLE CAREFULLY TO AVOID DISTORTION OF PCB TAILS.		
	2. CLEANING OF PARTS IN CHLORINATED SOLVENTS IS NOT PERMISSIBLE.		
A	I. MATES WITH COAXIAL PIN CONTACT SERI Notes:	ES 21-33122-54(), 21-33651-() & OTHERS.	TOLERANCES: .XXXX = ±.0005 ANGLES= .XXX = ±.010 .XX = ±.03 .X = ±.1
-	THE USE OF THIS DOCUMENT IS UNLIMITED. HOWEVER, DOCUMENTS REFERENCED HEREON MAY CONTAIN LIMITED RIGHTS DATA.	PRO/ENGINEER INFORMATION Pro/e Model Used:	DIM.& TOL. PER ASME YI4.5 DRM PER MIL-DTL-31000; OTHER Amphenol Stds. PER LEGENDS:
FORMAT: C-U_E-I	N / A RELEASED / May . 19 2008, 10:51 AM DOCUMENT NO. REV. 21-033430-021 SHEET 1 OF 1 A	NEXT ASSEMBLY NEXT ASSEMBLY 21-033430-021 21-033430-021 3	=FLAG NOTE CALL OUT REFERENCE ONLY

