
	4	3	
21-033450-051 SHEET 1 OF 1 A		$\begin{array}{c} & .300 \\000 \\282 \\ \pm .008 \\ 0.031 \\ \pm .002 \\031 \\ \pm .002 \\0200 \\ \pm .0005 \\274 \\001 \\0$	
B	 4. DRAWING ILLUSTRATES FINAL ASSEMBLY. INSTALLATION INSTRUCTIONS & HEATSHRI PACKAGED WITH EACH ASSEMBLY. PACKAG 3. MATERIALS: OUTER & INNER CONTACTS- BERYLLIU SHIELD FERRULE- BRASS PER ASTM B FRONT INSULATOR & SPACER INSULATC 2. FINISH: 	, DANIELS Y2039 DIE SET L, DANIELS KI777 POSITIONER TA MASTER QI50-24(I9)SS (I50 OHM) OR EQUIVALE CONTACT COMPONENTS ARE SHIPPED UNASSEMBLED. INK (NOT ILLUSTRATED) ARE GE PER PRODUCTION PROCESS SHEET. UM COPPER PER ASTM-B-I96 B453 OR QQ-B-626 OR- TFE RESIN PER ASTM 3651 II, GRADE C, CLASS I (.000050 MIN) .000050 MIN).	
FORMAT: C-U_E-I	NOTES: THE USE OF THIS DOCUMENT IS UNLIMITED. HOWEVER, DOCUMENTS REFERENCED HEREON MAY CONTAIN LIMITED RIGHTS DATA. N / A RELEASED / Mar . 22 2012, 11:31:34 AM	PE DIMENSIONAL REQUIREMENTS OF M39029/90.	



		, i				SCALE:	8.0		L - 40456 - 5	97	SHEET	I OF I	
R 9-3800	N / A					SIZE C	778	7820 21-03345		DOCUMENT NO	0-051	A REV.	0
.5M;	PROCESS SPEC.	C-I THIRD ANGLE PROJEC						TYPE M38999 I & III					O
		DESIGN MANAGER		HICKEY	- 9-Mar- 2 	9-Mar-12		CONTACT, PIN, QUADRAX, ELECTRICAL CONNECTOR,					21-033450-05
S= ±2°	N / A	PREPARED BY ENGINEER IN CH	ARGE	ORDEAU		AIVIF MEINOL CONFORATION 40-60 DELAWARE AVENUE SIDNEY, N.Y. 13838							
INCHES	MATERIAL SPEC.	APPROVALS			DATE AMPHENOL CORPORATION								
PECIFIED	SPECIFICATIONS	POS	POS QTY F			ART NUMBER DESCRIPTION							_
			4			70-002				CONTACT		NOTE	
		2	2	21	-03345	50-055			REAR IN	ISULATOR	?		SHEET
		3				50-053				NSULATO	R		
					I - 0 3 3 4 5 0 - 0 5 4			OUTER CONTACT					Ъ
		5			21-033450-058			SHIELD EXTENSION					_
					M23053/8-007-C 21-033450-056			SHIELD FERRULE				4	_¥ <
		8	1.5"		L-2119			INSTALLATION INSTRUCTIONS HEATSHRINK				4	-