


Dual Channel Small Form Factor Transceiver

26-pin high speed optical module card, 2x25Gbps



INTERCHANGABLE TO ALLOW FOR DUAL SOURCE

FEATURES

- Supports 2 Amphenol 1.25Gbps – 28Gbps Ruggedized SCFF Transceivers
- -40°C to 85°C operating temperature
- About 37 x 36 mm²
- Edge-card design with mechanical fixation features
- All individual signals routed to the edge connector
- SFF-8472 compliant two wire serial interface (I2C)
- Hard gold finish on edge-card contacts
- 2x LC Duplex – contact Amphenol for cable options
- Conformal coating for rugged applications
- Embedded CDR and BIT

BENEFITS

- Broad range of data rates for standard and non-standards protocols up to aggregate data rate of 2x25Gbps
- High-performance in harsh conditions
- Ideal for space-limited applications
- Robust easy-to-install (no soldering) pluggable design
- Highly versatile design with fully independent lines
- Easy access to transceivers for optimization and monitoring
- Extended remateability with performance variations
- Safe and easy optical connections

SUPPORTED STANDARDS

- 25Gbps Ethernet, 10Gbps, 1Gbps
- 1.25Gbps to 14Gbps (28Gbps) proprietary links
- 10GbE
- EDR Infiniband
- 8G/16G/32G Fiber Channel
- CPRI
- Other encoded interfaces

ORDERING INFORMATION

CF-170021-111	1-10Gbps Adapter card with 2x SCFF
CF-170021-112	1-25Gbps Adapter card with 2x SCFF

ELECTRICAL PERFORMANCE

- Power Supply Voltage: 3.3V
- Bit Error Rate
 - BER < 10^{-12} at 25GbE, PRBS31
 - BER < 10^{-12} at 10GbE, PRBS31
- Lanes per device: 2 Transmits and 2 Receives
- Low Power Consumption (< 2W @ 25Gbps)
- Transmitter Type: 850nm VCSEL Laser
- Receiver Type: PIN Photodiode
- Differential Impedance RF Lines: 100 Ohm $\pm 10\%$


ADDITIONAL INFORMATION

- Board Thickness: 1.57mm
- Mates with Samtec HSE8-109 connector family
- Hard gold finish for the edge-connect, other areas using ENEPIG
- All SCFF signals are routed separately to the Edge Connector
- Signals applied to the Edge Connector are mirrored on both sides to allow easier custom layout routing
- The SCFF housing is connected to the signal ground on the Edge Card


OPTICAL PERFORMANCE

- Operating Temp: -40°C to 85°C
- Storage Temp: -55°C to 100°C
- Typical Avg TX Power = 0.2dBm
- Typical RX Sensitivity = -12dBm (1E-12)
- Typical Power = 1.1W
- Power Supply = 3.3V
- Data Rate: 1Gbps to 25GbE
- Shock and Vibe: MIL-STD-883



SIGNAL TOP LAYER



SIGNAL BOTTOM LAYER



MECHANICAL PROPERTIES



Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors. AMPHENOL is a registered trademark of Amphenol Corporation. ©2023 Amphenol Corporation REV: PRELIMINARY



40-60 Delaware Avenue
Sidney, NY 13838
amphenol-aerospace.com | amphenolmao.com

Jared Sibrava • +1 (607) 643 - 1845 • jsibrava@amphenol-aa.com
amphenol-aerospace.com