

M1158 Series

AC/DC POWER SUPPLY



DESCRIPTION:

The M1158 military power supply is a rugged 3 phase AC to DC converter. It accepts a 115 AC input range from 100 to 140VAC, L-N, 50/60/400Hz and provides a single DC output from 5V to 50V, up to 500W, with custom outputs available. Designed to meet military standards, MIL-STD-810, MIL-STD-461.

FEATURES

- Miniature size
- High efficiency
- Wide input range
- BIT function
- Remote Inhibit (On/Off)
- Fixed switching freq. (~250 kHz)
- EMI filters included
- Power factor 0.86 at full load
- Designed for large capacitive loads
- Input / Outputs isolation
- Indefinite short circuit
- protection with auto-recovery
- Over temperature shutdown
- with auto-recovery

HOW TO ORDER

Part number	CF-02EM1158	AC/DC POWER SUPPLY
-------------	-------------	--------------------

PRODUCT SPECIFICATIONS:

AC INPUT	Nominal:	3-ph, 115 VAC,L-N, 60-400Hz
	Operating range:	100-140VAC,LN
Line/Load regulation	Up to $\pm 1\%$ (no load to full load, with load capacitance of 9.6mF $\pm 25\%$)	
Ripple and Noise	Less than 50mVp-p with 9.6mF load capacitance	
DC Output	Voltage range:	5 to 50 VDC
	Current:	0 to 25 A
	Power output:	0 to 500 W
Efficiency	89% minimum (at nominal line voltage, full load, room temperature)	
Turn on Transient	No voltage over shoot during power on.	
Isolation	Input to Output:	500 VDC
	Input to Case:	500 VDC
	Output to Case:	100 VDC
EMC	Designed to meet MIL-STD461F with static resistive load and shielded cables:	CE102 (with 12 dB relaxation below 30kHz), CS101, CS114, CS115, CS116, RE101, RE102, RS101, RS103

ENVIRONMENTAL CONDITIONS:

Temperature	Operating: -55°C to +85°C (at baseplate) Storage: -55°C to +125°C	
Fungus	IAW MIL-STD-810G Method 508.6	
Random Vibration	Frequency [Hz] 2 to 3.7 4 to 60 70 to 200 210 10000	Amplitude [g ² /Hz] 1x10 ⁻³ 2x10 ⁻³ 1x10 ⁻³ 1x10 ⁻⁵ 1x10 ⁻⁶
Low Pressure (Altitude)	IAW MIL-STD-810G Method 500.5 Procedure I – up to 40000 ft. Procedure II – up to 20000 ft.	
Sand and Dust	IAW MIL-STD-810G Method 510.5 Procedure I	
Vibration of Shipboard Equipment	IAW MIL-STD-167-1A Below Deck	
Humidity	IAW MIL-STD-810G Method 507.5 Up to 95%.	
Shock	IAW MIL-STD-810G Method 516.6 Procedure I, Figure 516.6-10 20 g, 11 ms terminal peak sawtooth (all directions)	
Reliability	150000 hours, calculated per MIL-STD-217F at +80°C base plate, Ground fixed.	
Environmental Stress Screening (ESS) Random vibration and thermal cycles ESS is available upon request. Please consult factory for details		

PROTECTIONS:

Input	Inrush current limiter
Output	Passive transorb on outputs. Current limiting Continuous protection for unlimited time.
General	Over temperature protection:Shutdown at base plate temperature of +95°C ± 5°C Automatic recovery at baseplate temperature greater than 85°C

PIN ASSIGNMENT:

Input Connector

Connector type: M24308/24-37F or eq.

Mates with: M24308/2-1F or eq.

Pin No.	Function
1	Phase A
2	N.C.
3	Phase B
4	Phase C
5	Chassis
6	Phase A
7	N.C.
8	Phase B
9	Phase C

Output Connector

Connector type: M24308/23-39F or eq.

Mates with: M24308/4-3F or eq.

Pin No.	Function
1	N/C
2	BIT (+)
3	INHIBIT (+)
4	VOUT RTN (-)
5	VOUT RTN (-)
6	VOUT RTN (-)
7	VOUT RTN (-)
8	VOUT RTN (-)
9	VOUT (+)

Pin No.	Function
10	VOUT (+)
11	VOUT (+)
12	VOUT (+)
13	VOUT (+)
14	N/C
15	BIT RTN (-)
16	VOUT RTN (-)
17	VOUT RTN (-)
18	VOUT RTN (-)

Pin No.	Function
19	VOUT RTN (-)
20	VOUT RTN (-)
21	VOUT (+)
22	VOUT (+)
23	VOUT (+)
24	VOUT (+)
25	VOUT (+)

FUNCTIONS AND SIGNALS:

INHIBIT

The INHIBIT signal turns the Outputs of the power supply ON and OFF.

OPEN ($I < 0.03 \text{ mA}$ @ $V = 6.2 \text{ V}$) – Output power available.

SHORT ($V < 2 \text{ V}$ @ $I = 2 \text{ mA}$) to VOUT RTN – Output power is inhibited.


BIT (Built-In Test)

Isolated open-collector transistor (Optocoupler secondary side).


Low ($V < 0.5 \text{ VDC}$ @ 2 mA): when output voltage rise above $95\% \pm 5\%$ off its nominal value.

Open ($I < 0.1 \text{ mA}$ @ 20 VDC max): when output voltage falls below $90\% \pm 5\%$ off its nominal value.

TYPICAL CONNECTION DIAGRAM:



OUTLINE DRAWING:



Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors.

AMPHENOL is a registered trademark of Amphenol Corporation.
PRELIMINARY

©2023 Amphenol Corporation REV:

Amphenol

MILITARY HIGH SPEED

40-60 Delaware Avenue
Sidney, NY 13838
amphenol-aerospace.com | amphenolmao.com

Jared Sibrava | +1 (607) 643-1845 | jsibrava@amphenol-aao.com
amphenol-aerospace.com